MATERIAL SAFETY DATA SHEET

Manufacturer's Name:

Masterchem®Industries, Inc.

3135 Old Highway M Imperial, MO 63052 Company Code: MTER Issue Date: October 10, 2001

Transportation Emergencies: Call Chemtrec 1-800-424-9300 Emergency Telephone No. $\begin{array}{ccc} \text{NPCA HAZARDOUS MATERIALS IDENTIFICATION SYSTEM} \\ \underline{\text{RATING}} & \underline{\text{IDENTIFICATION}} \\ 4 = \text{EXTREME} & \text{HEALTH} & 2 \end{array}$ 3 = HIGH 2 = MODERATE FLAMMABILITY REACTIVITY 1 = SLIGHT 0 = MINIMA CHRONIC HEALTH SEE SECTION V

1-800-325-3552 Medical Emergencies: 1-800-228-5635 Ext. 219

SECTION I - PRODUCT IDENTIFICATION

Kilz® Total One® - One Gallon Can PRODUCT NAME:

51652-13001-0 PRODUCT NUMBER:

		SEC	CTION II A-HAZAR	DOUS INC	FRED	IENTS		
CAS REGISTRY NO.	%W	CHEMICAL NAME(S)		OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE	LISTED AS A CARCINOGEN	
				TL	V	PEL		
107-21-1	3.56	Ethylene Glycol		50 pp	m	50 ppm	0.06 mm Hg @ 20°C	No
		S	ECTION II B - OTH	ER INGR	EDIE	NTS		
Proprietary	45-60	Acrylic Resin Emulsion				-	-	No
7732-18-5	10-25	Water		-		-	-	No
13463-67-7	10-20	Titanium Dioxide		-		-	-	No
1317-65-3	10-20	Calcium Carbonate		-		-	-	No
			SECTION III - PI	HYSICAL	DATA	4		
APPEARANCE: White, Medium Viscosity Liquid				ODOR: Characteristic Acrylic				
BOILING RANGE: 212°F				VAPOR DENSITY: ☑ HEAVIER ☐ LIGHTER THAN AIR				
EVAPORATION RATE: ☐ FASTER ☒ SLOWER THAN ETHER				60.88% VOLATILE VOLUME: 10.93 POUNDS WT/GAL				
		SECTION	N IV - FIRE AND EX	PLOSION	HAZ	ZARD DAT	ΓA	
FLAMMABILITY CLASSIFICATION: None F			FLASH POINT: None	H POINT: None LEL: N/A			DOT: Not regulated	
			EXTINGUISH	ING MEDIA	.:		1	
DRY CHEMICAL	X ALCO	HOL FOAM 🗵	WATER FOG 🗵	FOAN	ıΣ		CO ₂ 🗵	OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS: This product will not burn, however dried primer film will support combustion.

SPECIAL FIREFIGHTING PROCEDURES: Firefighters and others exposed to products of combustion should wear self-contained breathing apparatus and full protective clothing. Use water to keep fire-exposed containers cool to reduce pressure.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: Inhalation: May cause irritation to upper respiratory tract. Shortness of breath and dizziness. Splash (Eyes): Can cause irritation, burning and redness. Splash (Skin): Prolonged or repeated contact may cause minor irritation. Ingestion: Gastrointestinal distress, may be harmful if swallowed in large amounts.

DDIMADY	Y ROUTE(S)	OF FNTDV

TRANSMIT ROUTE(b) OF ENTRY.						
DERMAL ⊠	INHALATION 区	INGESTION 🗵				

EMERGENCY AND FIRST AID PROCEDURES: Inhalation: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician. Splash (eyes): Flush immediately with large amounts of water for at least 15 minutes. Take to physician for medical treatment. Splash (skin); Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. Ingestion: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult physician or poison control center immediately. Treat symptomatically.

SECTION VI - REACTIVITY DATA

STABILITY: UNSTABLE \square STABLE \boxtimes

HAZARDOUS POLYMERIZATION: MAY OCCUR \square WILL NOT OCCUR \boxtimes

HAZARDOUS DECOMPOSITION PRODUCTS: May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain: carbon monoxide, carbon dioxide, hydrocarbons and other products of combustion.

CONDITIONS TO AVOID: High Temperatures or high humidities. Heat, sparks, or open flame.

INCOMPATIBILITY: (MATERIALS TO AVOID) Peroxides or strong oxidizing agents.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Limit spread of spill or leak. Ventilate area. Soak up with inert absorbent material and transfer to closed containers. See Section VIII for required protective measures. Keep material out of sewers and/or drains.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations. Dry product and empty containers may be landfilled. Full or partially full containers should be dried or coagulated with the liquid portion poured off. Coagulated material should be dried before landfilling. Product may also be incinerated.

SECTION VIII-SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or Equivalent) or leave the area.

VENTILATION: Ventilation of sufficient volume and pattern should be provided to minimize exposure. Local exhaust ventilation required when working in a confined area.

PROTECTIVE GLOVES: Required, rubber or neoprene to prevent skin contact.

EYE PROTECTION: Use safety eyewear including splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing. Remove and wash contaminated clothing before re-use.

HYGIENIC PRACTICES: Wash hands before eating or using the washroom. Smoke in smoking areas only.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in accordance with OSHA 1910.106. Store in well ventilated areas. Protect from freezing. Frozen product may coagulate and become unusable.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. Avoid prolonged contact with skin. Keep closure tight and container upright to prevent leakage. Do not store near heat, sparks, or open flame. Do not breathe spray. Containers must not be washed out or used for other purposes. Avoid contact with or breathing of vapors released during curing process. Do not remove or deface container label. Keep out of the reach of children.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The product is no more hazardous than its component parts pursuant to 29CFR 1910.1200 (D). The technical information on this MSDS sheet is based upon information submitted by manufacturers and additional information furnished by distributor's chemical suppliers and manufacturers. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

PREPARED BY: Mr. William R. Benton	DATE PREPARED: October 10, 2001
NAME AND TITLE: W.R. Benton, MSDS Coordinator	SUPERSEDES: September 26, 2000 TO gal

(Signature Available upon Request)